Boxmaker Series- Similarities and differences

	BM2508 Plus	BM2508 SE	BM3000
Corrugated board type	Sheets Or Fanfold (Single , Double wall)	Sheets (Single , Double wall)	Sheets Or Fanfold (Single , Double wall)
Cardboard thickness	2-10mm	2-10mm	2-10mm
Cardboard density range	Up to 1200g/m²	Up to 1200g/m²	Up to 1200g/m²
Max.board size	2500mm width x unlimited length	2500mm width x unlimited length	3000mm width x unlimited length
Min.board size	200mm width x 650mm length	200mm width x 650mm length	300mm width x 650mm length
Production Capacity	Appr.7-10 pcs/minute	Appr.7-10 pcs/minute	Appr.8-12 pcs/minute
	Depends on size and box style.	Depends on size and box style.	Depends on size and box style.
Slotting Knife	2 pcs *500mm Length	2 pcs *500mm Length	2 pcs *500mm Length
Vertical Cutting knife	4	4	4
Scoring/Creasing wheel	4	2 (Option 4)	4
Horizontal Cutting knife	1	1	1
Power supply	BM2508-Plus 380V±10%，Max. 3.5kW, 50/60 Hz	BM2508-SE 380V±10%，Max. 2.5kW, 50/60 Hz	BM3000 380V±10%，Max. 4kW, 50/60 Hz
	Vacuum Pump 380V±10%，Max. 3.7kW, 50/60 Hz	Vacuum Pump 380V±10%，Max. 3.7kW, 50/60 Hz	Vacuum Pump 380V±10%，Max. 5.5kW, 50/60 Hz
Air Pressure	0.6-0.7MPa	0.6-0.7MPa	0.6-0.7MPa
Dimension	3500(W) * 2100（L）* 2030mm(H)	3330(W) * 1800（L）* 2000mm(H)	3700(W) * 1750（L）* 2030mm(H)
Gross Weight	Appr.3500Kg	Appr.2800Kg	Appr.3500Kg
Automatic paper feeding	Lead edge feeder 1400mm	Lead edge feeder 900mm	Lead edge feeder 1400mm
Handhole on box sides	Hand hole module size (120*120mm)	NO	Hand hole module size (120*120mm)
Air Consumption	75L/Min	40L/Min	75L/Min
Box styles	More than 60 Fefco codes	About 25 Fefco codes	More than 60 Fefco codes
All the above specifications are for reference only.			
The final interpretation right belongs to Qingdao Aopack On Demand Packaging co., Ltd.			